17025 SO. MAIN ST. GARDENA, CA 90248 800.572.9029
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 stepstoneprecast.com

### MATERIAL PRODUCT DATA SHEET

### **Product Name**

Lightweight Roof Paver

# Manufacturer

 Stepstone, LLC
 Phone
 310-327-7474

 17025 So. Main St.
 Fax
 310-217-1424

 Gardena, CA 90248
 Toll Free
 800-572-9029

## **Product Description**

Stepstone has produced high quality precast concrete since 1963. Lightweight Roof Pavers are 1 inch hardrock concrete backed with 1½ inches of 25 LBS expanded polystyrene foam. Lightweight Roof Pavers are designed to be used in lightweight installations for both commercial and residential applications.

## **Composition & Materials**

Lightweight Roof Pavers are hand-made, wet-cast from 5000 PSI hard rock concrete using Type III cement.

#### Sizes

Lightweight Roof Pavers are available in 23-7/8"x 23-7/8"x 2-1/2" standard. Custom sizes are available upon request.

## **Finishes**

Lightweight Roof Pavers available finishes include: Custom Aggregates, Sonorastone® slate finish, light, medium, or heavy sandblast.

# **Colors**

Lightweight Roof Pavers are available in 12 standard colors: Adobe, Agave, Almond, Brick Red, Cafe Brown, Caramel, French Gray, Granada White, Iceberg Green, Kona, Pebble and Porcelain; custom colors are available upon request.

## **Technical Data**

APPLICABLE STANDARDS: American Society for Testing & Materials (ASTM)

ASTM C33 - Standard Specification for Concrete Aggregates

ASTM C39 - Concrete Compressive Strength

ASTM C150 - Standard Specification for Portland Cement

ASTM C642 - Water Absorption, Density, Voids in Hardened Concrete

ASTM C666 - Rapid Freeze/Thaw Resistance of Concrete

ASTM C979 - Pigments for Integrally Colored Concrete

ASTM C1028 - Coefficient of Friction

## **Physical/Chemical Properties**

Lightweight Roof Paver weight is 12 LBS per square foot. Water absorption Not more than 6.0% average, not more than 7.0% for any individual unit for standard colors. Unit length, width and height are not more than +/-1/8" from standard dimensions. No unit will differ more than +/-1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.