MATERIAL PRODUCT DATA SHEET

Product Name

Rooftrac

Manufacturer

 Stepstone, LLC
 Phone
 310-327-7474

 17025 So. Main St.
 Fax
 310-217-1424

 Gardena, CA 90248
 Toll free
 800-572-9029

Product Description

Stepstone has produced high quality precast concrete since 1963. Rooftrac is a planking system that creates a runway around the roof perimeter to ease the movement of the window washing equipment. Rooftrac planking is reinforced with zinc plated welded wire fabric reinforcing. Rooftrac is well suited for condominiums, apartments, and office buildings.

Composition & Materials

Rooftrac is hand-made, wet-cast from 5000 PSI hard rock concrete using Type III cement.

Sizes

Rooftrac is available in 12"x48"x 2-1/2"

Finishes

Rooftrac available in broom finish.

Colors

Rooftrac is available in Granada White; custom colors are available upon request.

Technical Data

APPLICABLE STANDARDS: American Society for Testing & Materials (ASTM)

ASTM C33 - Standard Specification for Concrete Aggregates

ASTM C39 - Concrete Compressive Strength

ASTM C150 - Standard Specification for Portland Cement

ASTM C642 - Water Absorption, Density, Voids in Hardened Concrete

ASTM C666 - Rapid Freeze/Thaw Resistance of Concrete

ASTM C979 - Pigments for Integrally Colored Concrete

ASTM C1028 - Coefficient of Friction

Physical / Chemical Properties

Rooftrac weight is 28 LBS per Square foot. Water absorption: Not more than 6.0% average, not more than 7.0% for any individual unit for standard colors. Unit length, width and height are not more than +/-1/8" from standard dimensions. No unit will differ more than +/-1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.