

- 1. PAVERS SHOWN ABOVE SHALL BE 2 1/2"THICK; ALL SIZES ARE NOMINAL
- 2. PAVERS SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 5,000 PSI
- 3. PAVERS CAN BE MORTAR SET OR SAND SET
- 4. MADERASTONE® FINISH (WOOD GRAIN LOOK)
- 5. PAVERS ARE AVAILABLE IN TWELVE (12) STANDARD COLORS; CUSTOM COLORS AND SIZES MAY BE AVAILABLE UPON REQUEST
- 6. ALL SIDES HAVE DRAFT; SEE SPECIFICATIONS FOR TOLERANCES



MADERASTONE® PAVER - GENERAL DETAILS

SCALE: N.T.S.


PAGE 7

800.572.9029

STEPSTONEPRECAST.COM




CALARC® DIVISION



1/4"WIDTH, 3/16" DEPTH

ISOMETRIC VIEW



- 1. PAVERS SHOWN ABOVE SHALL BE 2"THICK; ALL SIZES ARE NOMINAL
- 2. PAVERS SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 5,000 PSI
- 3. PAVERS CAN BE MORTAR SET OR SAND SET
- 4. MADERASTONE® FINISH (WOOD GRAIN LOOK)
- 5. PAVERS ARE AVAILABLE IN TWELVE (12) STANDARD COLORS; CUSTOM COLORS AND SIZES MAY BE AVAILABLE UPON REQUEST
- 6. ALL SIDES HAVE DRAFT; SEE SPECIFICATIONS FOR TOLERANCES



MADERASTONE® PAVER - GENERAL DETAILS

SCALE: N.T.S.

PAGE 8

800.572.9029

STEPSTONEPRECAST.COM